

SPECIFICATION

For

SWITCHING POWER SUPPLY

M/N: MPE-S106(-SB)-B(-C)

Revision History

[illegible]

MPE-S106(-SB)-B(-C)

100W AC / DC



FEATURES

- ✓ 115W fan cooling, 100W with convection-cooled of single output power supply.
- ✓ Compact size 2 x 4 inch and low profile.
- ✓ High efficiency up to 90%.
- ✓ No-load power consumption < 0.5W.
- ✓ Optional +5Vsb and remote on/off function.
- ✓ Class II, also class I with optional functional ground connected.
- ✓ ITE safety standard IEC 62368-1, UL 62368-1 approved.
- ✓ Meets EMI CISPR/FCC class B.
- ✓ PFC meet EN 61000-3-2 Class A and EN 61000-3-3.



Models & Ratings

Model Number	Wattage (Rated / Max)	Output Voltage		Min. Current	Rated Current	Max. Current
MPE-S106-B	100 W / 115 W	+48 V		0 A	2.09 A	2.4 A
MPE-S106-SB-B	100 W / 115 W	V1	+48 V	0 A	2.09 A	2.4 A
		V2	+5 V	0 A	-	0.5 A

Total Output Power: Max. 100W convection cooled, max. 115W with 7 CFM at 50°C; max. 100W with 7 CFM at 70°C environment temperature.

1. MAX output current can be sustained if the total power doesn't exceed 100W.

2. Model no. coding:

MPE-S106-X-B-Y-Z



1	X=	Output set	2	B=	62368-1 Approved	3	Y=	Connector Type	4	Z=	Mechanical
	blank	Single output					blank	Molex Type Connector or equivalent		blank	Open frame
	SB	Dual output (with +5Vsb & remote on/off function)					J	JST Type Connector or equivalent		C	Optional cover kit

Note: Main label just show 5Vsb or not.

Summary

Characteristic	Minimum	Typical	Maximum	Units	Notes & Conditions
Input Range	85	115 / 230	264	VAC	Continuous input range.
Input Frequency	47	50 / 60	63	Hz	AC input.
Efficiency	88	90		%	At input 230VAC, rated load, above 1hr. warm up.
Operation Temperature	-20		+70	°C	See the following performance curves for the detail.
Weight		85		g	-SB model is 86.5 g.
Dimensions	101.6 (L) x 50.8 (W) x 34.2 (H) mm, Tolerance +/- 0.4mm.				
EMC	EN 55022 / EN 55032, CISPR 22 & FCC Part 15, EN 61000-3-2, EN 61000-3-3, EN 61204-3, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11				
Safety Approvals	IEC 60950-1, 2 nd Edition, EN 60950-1, 2 nd Edition, UL 60950-1, 2 nd Edition, CSA C22.2 No. 60950-1-07, 2 nd Edition IEC 62368-1, UL 62368-1, 2 nd Edition, CSA C22.2 No. 62368-1-14, 2 nd Edition				

Input

Characteristic	Minimum	Typical	Maximum	Units	Notes & Conditions
Input Voltage	85	115 / 230	264	VAC	Continuous input range.
Input Frequency	47	50 / 60	63	Hz	AC input.
Input Current			2.5	A	Nominal AC Input Voltage (115VAC), rated load.
Inrush Current			30 / 60	A	Nominal AC Input Voltage (115VAC/230VAC), one cycle at 25°C cold start.
No-load power consumption			<0.5	W	Nominal AC Input Voltage (115VAC/230VAC). Only with model MPE-S106-B.
Input Protection	One non-user serviceable internally located AC input line fuse. Fuse : 3.15A / 250VAC * 1pcs				

Output

Characteristic	Minimum	Typical	Maximum	Units	Notes & Conditions
Output Voltage		+48 V		DC	
		+5Vsb			
Output Current		2.09	2.4 ^(V1)	A	
			0.5 ^(V2)		
Initial Set Accuracy		±1.0 ^(V1) ±2.5 ^(V2)		%	Initial setting accuracy is adjusted at input 115VAC and output at 60% rated load.
Minimum Load		0		A	
Start Up Delay		0.5	1	Sec	Time required for initial output voltage stabilization.
Hold Up Time	10 / 40			mS	Nominal AC Input Voltage (115VAC/230VAC), rated load.
Line Regulation		±1.0 ^(V1) ±1.0 ^(V2)		%	Less than ±1% at rated load with ±10% changing in input voltage 115VAC.
Load Regulation		±1.0 ^(V1) ±1.0 ^(V2)		%	Measured from 60% to 100% rated load and from 60% to 20% rated load (60% ±40% rated load).
Ripple & Noise		480 ^(V1) 50 ^(V2)		mV	Measured at rated load by a 20MHz bandwidth limited oscilloscope and the each output is connected with a 10µF Electrolytic Capacitor and a 0.1µF Ceramic Capacitor.
Leakage Current			0.25	mA	At input 264VAC, 63Hz, rated load.
Overvoltage Protection	For some reason the power supply fails to control itself, the build-in over voltage protection circuit will auto recovery the outputs to prevent damaging external circuits, the trigger point is around 110%~135% of output voltage.				
Short Circuit Protection	Fully protected against output overload and short circuit. Automatic recovery upon of overload condition.				
Remote On / Off	The power supply will be turned on when the power On/Off pin is connected to secondary GND. This function exists only with optional +5Vsb.				


General

Characteristic		Minimum	Typical	Maximum	Units	Notes & Conditions
Efficiency		88	90		%	At input 230VAC, rated load, above 1hr. warm up.
Isolation	IP to OP	3000			VAC	
	IP to GND	1800			VAC	
Switching Frequency			65		KHZ	

Environmental

Characteristic		Minimum	Typical	Maximum	Units	Notes & Conditions
Operating Temperature		-20		+70	°C	See the following performance curves for the detail.
Storage Temperature		-40		+85	°C	
Relative Humidity		5		95	%RH	Non-condensing.
Cooling		7			CFM	Forced-cooled when 100W~115W.
Operating / Non-Operating Altitude			3000 / 4000		m	



Derating curve



Note:

1. Air flow from IC3 to the body of PSU with distance 50mm maximum.

With optional cover (MPE-S106(-SB)-B-C)



EMC: Emissions

Phenomenon	Standard	Class	Notes & Conditions
Conducted	EN 55022 / EN 55032 CISPR 22 & FCC Part 15	B	
Radiated	EN 55022 / EN 55032 CISPR 22 & FCC Part 15	B	
Harmonic Current	EN 61000-3-2	A	
Voltage Fluctuations	EN 61000-3-3		
Voltage Flicker	EN 61204-3	B	

EMC: Immunity

Phenomenon	Standard	Criteria	Notes & Conditions
ESD	IEC 61000-4-2	A	±8KV air discharge, ±6KV contact discharge
Radiated	IEC 61000-4-3	A	10V/m
EFT	IEC 61000-4-4	A	±2KV Line & PE
Surges	IEC 61000-4-5	A	L-N:±1KV, L/N-PE:±2KV
Conducted	IEC 61000-4-6	A	10V
Power Magnetic	IEC 61000-4-8	A	10A/m
Dips and Interruptions	IEC 61000-4-11	A A A / B C	DIP: >95%, 0.5 cycle DIP: 30%, 25 cycles DIP: 60%, 5 cycles (Note 2.) INT: >95%, 250 cycles

Note:

- As a build-in type power supply, the power supply needs to be installed in a suitable enclosure to pass the EMI/EMC tests.
The final assembly has to comply with the valid EMI/EMC and safety.
- The test result of input 240Vac / 100Vac is criteria A / B.
- The mounting holes should be connected to each other to conform the EMI limit.

Safety Approvals


Safety Agency	Safety Standard	Notes & Conditions
TUV	EN 62368-1, 2nd Edition(Design to meet)	CE(LVD) declaration.
	EN 60950-1, 2nd Edition(Design to meet)	
CB	IEC 62368-1, 2nd Edition	
	IEC 60950-1, 2nd Edition	
UL/cUL	UL 62368-1, 2nd Edition, CSA C22.2 No. 62368-1-14, 2nd Edition	UL, cUL approved..
	UL 60950-1, 2nd Edition, CSA C22.2 No. 60950-1-07, 2nd Edition	

Mechanical Details

M/N: MPE-S106-SB-B

Unit: mm

SIZE : 101.6(L) x 50.8(W) x 34.2(H)mm, Tolerance +/-0.4mm.




Note: The installation shall be kept in an isolation distance min. 2.8mm between the unit and the system chassis. There exist hazardous voltage in dotted area, keep insulating to avoid hazardous electric shock.

MPE-S106(-SB)-B(-C)

100W AC / DC

For m/n: MPE-S106(-SB)-B-C
Unit: mm Tolerance: +/- 0.4mm



MPE-S106(-SB)-B(-C)

100W AC / DC

Parameter	Conditions/Description					
Dimension	101.6 (L) x 50.8 (W) x 34.2 (H) mm, Tolerance +/- 0.4mm.					
Connector & Pin Assignment	Location	Pin (Note 1)		Assignment	Proposed Housing	Proposed Terminals
CN1(Input) molex 09-65-2038 or equivalent (remove the middle pin)		MX1	JT2	AC in (N)	a. MOLEX: 09-50-1031 (5195-03) or 09-52-4034 (5239-03) or equivalent	a. MOLEX :5194 or 5225 2478, 2578,5167 or 5168 or equivalent
		MX2	JT1	AC in (L)	b. JST: VHR-3N or equivalent (Note 2)	b. JST: SVH-21T-P1.1 or equivalent
CN2(Output) molex 09-65-2048 or equivalent		MX1	JT4	0 V	a. MOLEX: 09-50-1041 (5195-04) or 09-52-4044 (5239-04) or equivalent	a. MOLEX:5194 or 5225 2478, 2578,5167 or 5168 or equivalent
		MX2	JT3	0 V		
		MX3	JT2	+ V	b. JST: VHR-4N or equivalent (Note 2)	b. JST: SVH-21T-P1.1 or equivalent
		MX4	JT1	+ V		
CN3(Note 3) molex 22-04-1031 or equivalent		MX1	JT3	+5Vsb	a. MOLEX: 22-01-1032 (5051-03) or 51191-0300 or equivalent	a. MOLEX:2759 or 5159 or 50802 or equivalent
		MX2	JT2	0 V		
		MX3	JT1	RC	b. JST: XHP-3 or equivalent (Note 2)	b. JST: SXH-001T-P0.6N, SXH-001T-P0.6 or SXH-002T-P0.6 or equivalent

Note:1. The pin assignment "MX" for Molex type connector or equivalent, "JT" for JST type connector.

2. Exist with model no. suffixed -J, please see the Model no. coding.

3. Exist with model no. suffixed -SB, please see the Model no. coding.

Labeling

The labeling of MPE-S106(-SB)-B is shown below for reference.



Thermal Considerations

In order to ensure safe operation of the PSU in the end-use equipment, the temperature of the components listed in the table below must not be exceeded.

Temperature should be monitored using J type thermocouples placed on the hottest part of the component (out of any direct air flow). See Mechanical Details for component locations.

Temperature Measurements at max. amb.	
Component	Max Temperature
T1	110°C
Q1	120°C
D5,D6	120°C
C2	105°C
C21	105°C